

KAL760

Kilsen Addressable Input Module - 1 Input

General

The KAL700 series modules consists of a complete range of interfaces developed for I/O control on Kilsen addressable fire systems, housed in easy to install, IP55 housings. These modules allow the fire system to perform additional building management functions during fire situations. 125 I/O addresses are available on every fire panel loop in addition to 125 fire detector addresses.

Input Module

The KAL760 is an addressable, single input unit for Kilsen addressable fire systems. It provides a remote input to the fire system loop that is constantly monitored for open and short circuit conditions. The input may be activated by closing a potential free contact.

Installation

The KAL700 Series is designed for surface mount installation. Addressing on the modules is done via easy to use DIP switches.

Applications

The KAL760 may be used to monitor both pre-alarm and alarm states of any potential free contact and report this status to the fire control panel e.g. the monitoring of pressure equipment, aspiration systems, flow switches, doors, etc.



Details

- EN54:18 and CPD certified
- Surface mount
- Easy addressing
- External or loop powered
- Local alarm and communications indication
- Normally open switch supervision
- Part of a family of I/O modules consisting of: -Conventional zone monitors -Digital input modules -Extinguishing control modules -Loop Isolators -Manual call points -Relay and supervised output units -Fire door controllers

KAL760

Kilsen Addressable Input Module - 1 Input

Technical specifications

General

Status indication	LED
Compatibility	Kilsen KL7A systems

Electrical

Power supply type	24 VDC
Operating voltage	22 to 38 VDC
Current consumption	Loop power: 750 μ A (Quiescent) < 3.6 mA (Active) External power: 110 μ A @ 24 VDC from the loop (Quiescent) 135 μ A @ 35 VDC from the loop (Quiescent) 200 μ A (Quiescent) < 10 mA (Active)

Input

Input quantity	1
Input type and rating	Supervised
Input states	Active, Normal, Open, Short
Termination resistor	270 k Ω
Resistor: Pre-alarm	100 k Ω
Resistor: Alarm	39 k Ω

Physical

Physical dimensions	150 x 110 x 70 mm
Net weight	370 g
Colour	Grey
Mounting type	19" rack, Surface mount
Cable entries	10

Environmental

Vandal proof	No
Operating temperature	-10 to +50°C
Storage temperature	-10 to +70°C
Relative humidity	10 to 95% noncondensing
Environment	Indoor
IP rating	IP55

Standards & regulation

Compliance	CE, REACH, RoHS 2, WEEE
Certification	CPR
Standards	EN54-18

